




RECOMMENDED P.C.B OARD LAYOUT (T=1.6MM)
PCB TOLERANCE:±0.05



NOTES:

1. Material:

Housing: NY46, UL 94V-0 Rated.

Color: Gray.

Contact: Brass C2680.

Plating: Tin Plating 100u" Min. Over All,
Nickel Under Plating 50u" Min. Over All.

2. Electrical Specification:

Voltage Rating: 250V AC/DC.

Current Rating: 9Ampere AC/DC.

Contact Resistance: 20mΩ Max.

Insulation Resistance: 1000MΩ Min.

Dielectric Withstanding Voltage: 1500V AC per Minute.

3. Environmental:

Operating Temperature: -40°C to +105°C

Part Number:

CATX-M24VDT3-5H

ATX Power Series
M: Male Type
24: 24Pins
(2x12P)
V: Vertical Type
H: Without Post
Long Latch=46.2mm
5: Pin Row=5.5mm
3: Gray Color
T: Tin Plating
D: DIP Type

A	11/02/05	RELEASED FOR PRODUCTION	
REV	DATE	DESCRIPTION	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MM TOLERANCES ARE:		CAD GENERATED DRAWING, DO NOT MANUALLY UPDATE	
DECIMALS	ANGLES	APPROVALS	DATE
.X ± .38	± 3°	DRAWN Chris	11/02/05
.XX ± .25		CHECKED Cindy	11/02/05
.XXX ± .20		APPV Jason	11/02/05
DO NOT SCALE DRAWING		SHEET 1 OF 1	SCALE NONE
		DWG. NO. CATX-M24-05H	REV. A



凱聯科技股份有限公司
Conn-Link Technology Inc.

DESCRIPTION ATX Power, 24Pins(2x12P), Vertical, DIP Type
Pin Row 5.5x4.2mm, Without Post, Long Latch=46.2mm