

T:1.6 Dimensions of PC board holes
Tolerance : ±0.1(Printed-Top view)

Specification:

1. Rating: DC 24V 3A
2. Contact Resistance: 0.03Ω Max.
After Life Test: 0.05Ω Max.
3. Insulation Resistance: 100MΩ Min. (500V DC)
After Life Test: 50MΩ Min.
4. Withstand Voltage: 500V AC.
5. Insertion and Extraction Force: 3N~30N.
6. Life Test: 5,000 Cycles Min.
7. Operation Temperature Range: -20°C~70°C.
8. Respiration Temperature Range: -40°C~85°C.

Part Number:


CDCJ-073RDG0-84

DC Power Jack
XX: Center Pin
07:0.75mm/5.0mm

84: Product Number
0: Black Color
G: Gold Flash
D: DIP Type
R: Right Angle
3: 3Pins

6	DETECT PIN	1	COPPER ALLOY	MB:Ni Matte Tin
5	POWER PIN	1	COPPER ALLOY	MB:Ni Gold Flash
4	GROUND PIN 2	1	COPPER ALLOY	MB:Ni Gold Flash
3	GROUND PIN 1	1	COPPER ALLOY	MB:Ni Gold Flash
2	SHELL	1	COPPER ALLOY	Ni Plating
1	HOUSING	1	HIGH TEMP, UL94V-0	BLACK

NO.	DESCRIPTION	QTY	MATERIAL	REMARK
1		2	3	4

A	03/30/15	RELEASED FOR PRODUCTION		
REV	DATE	DESCRIPTION		
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MM TOLERANCES ARE:		CAD GENERATED DRAWING, DO NOT MANUALLY UPDATE		
DECIMALS	ANGLES	APPROVALS	DATE	 凱聯科技股份有限公司 Conn-Link Technology Inc.
.X ± .38	± 3°	DRAWN	Chris	
.XX ± .25		CHECKED	Cindy	
.XXX ± .20		APPV	Jason	
DO NOT SCALE DRAWING		SHEET	1 OF 1	
		SCALE	NONE	DESCRIPTION
		DWG. NO.	CDCJ-073-084	DC Power Jack, Center Pin 0.75mm/5.0mm Right Angle, DIP, Gold Flash, With Shell, Black
		REV.	A	