



Connectors Specialist, We Connect Your Quality Systems.

Cables Assembly, We Link Your Innovation Projects.





Connectors Specialist, We Connect Your Quality Systems.

Cables Assembly, We Link Your Innovation Projects.

凱聯科技股份有限公司秉持著「創新設計以聯結客戶服務」的精神，提供全世界的先進們最優質的服務與產品的技術支援。

凱聯科技主要提供電子零組件的產品與研發支援；我們的工廠均有多年的研發經驗、並以長期 OEM 與 ODM 的經驗累積，以創新與品質為主軸，發展符合客戶應用與市場需求的電子零件。以電子連接器、轉接頭與線材為主，我們的產品遍及全球電子商品；蓋括手機、電腦主機、筆記型電腦、平板電腦、電視機、數位機上盒、數位家電產品、網路通訊產業、工業控制電腦、收銀系統、儲備系統，以及雲端管理系統等。

連接器及線材是電子產品不可或缺的主要零組件之一，凱聯團隊以多年的電子產品的服務經驗，依客戶的需求提供最佳的技術支援與高品質的產品服務，讓客戶在設計及研發電子產品時，能夠取得豐富且有效益的市場資訊，更可以無後顧之憂的資源來開發產品，以創造雙贏互助的產業合作。

凱聯的產品研發，除了以先進、創新與品質為發展目標，更進而提倡綠能環保，創造一個愛護與守護地球的產業資源；因此，我們的產品均符合全球環保要求的 RoHS 環保規範，目前也有多數產品已達到 REACH 與無鹵等環保品質規章的要求。

我們擁有完善的合作團隊，從研發技術、模具開發、塑膠射出、端子沖壓及電鍍到組裝，都有雄厚的基礎與經驗；由專業的設計、到品質的管控、以及完整的供應鏈，致使我們的產品應用可以遍佈於全球精密工業產業與電子科技產品。以之於凱聯能夠提供客戶最有價值的產品品質與最具競爭力的產品服務。

讓凱聯科技連接您高品質的產品機種，同時也連結您超先進的產業系統。





Connectors Specialist, We Connect Your Quality Systems.
Cables Assembly, We Link Your Innovation Projects.

Conn-Link Technology Inc. holds the spirit of “Innovation Design Links Customer Service” to provide the best service and suppose the technology on electronic components and electrical products.

Because of long-term OEM and ODM service, Conn-Link had accumulated vast experience of tooling design. We research and develop the technologies for customization and marketing application based on the principle of innovation and quality.

Conn-Link designs and makes the electronic components and electrical parts. We focus in Connectors, Adaptors, Cables Assembly, RF Antenna Coaxial, and SSD Case etc. Our products are application at the Electronic Products all over the world, including, Mobile Phone, Desktop(Personal Computer), Lagtop(Notebook), Netbook, Tablet PC, Digital TV, Set-Top-Box, Digital Household Appliance Products, Network Communications Products, Industrial PC (IPC), POS System, Storage System, and Could Computing System etc.

For better suppose and closer relationship with worldwide clients, we also search the strong sales partners all over the world. Conn-Link creates good service team in every country, and serves all our customers a better support and faster respond time.

Conn-Link’ s products not only produce at Innovation and Quality, but also stress the Green Environment. We hope to create an ECO production resource, thus, all of our products are RoHS compliance, and most are REACH and Halogen Free.

We have a very complete co-work group; from R&D technology, tooling design, plastic injection, terminal stamping, plating to assembly production line, we all have strong basic and experience. Start from professional design to quality control and full supply chain. That’ s why our products are application all over the world.

Cause of the powerful co-workers, we assure to provide good quality, good delivery, and competitive price. Based on the valuable production quality and competitive service, Conn-Link is the first choice of your co-operation partnership.



Connectors Specialist, We Connect Your Quality Systems.

Cables Assembly, We Link Your Innovation Projects.

Index

• Company Profile	P1~P2
• Index	P3
• Serial ATA 7P Connectors	P4
• Serial ATA 22P Male Connectors	P5
• Serial ATA 22P Female Connectors	P6
• Micro SATA 16P Connectors	P7
• Slim Line SATA 13P Connectors	P7
• eSATA (external SATA) Connectors	P8
• SAS (Serial SCSI) Connectors	P9
• HDMI (High Definition Multimedia Interface) Connectors	P10
• Display Connectors	P11
• USB Connectors	P12
• USB3.0 Connectors	P13
• DC Power Jack (DIP Type)	P14
• DC Power Jack (SMT Type)	P15
• Power Connectors	P15
• 3.5mm Earphone Jack	P16
• 2.5mm Earphone Jack	P17
• D-SUB Connector	P17
• RJ Modular Jack	P18~P19
• Optical Jack	P19
• Pin Header	P20
• Box Header	P21
• Female Header	P22
• Wire to Board Connectors (Wafer)	P23
• FPC ZIF Connectors	P23
• Cable Assembly	P24
• Equipments	P25
• Quality Assurance	P26



Serial ATA 7P Connectors



CSAT-M07VDG0-A2

- ▶ Vertical DIP, Type A Footprint
- ▶ A2: Pin=2.15~2.3mm; A3: Pin=3.3mm
- ▶ Color Options: Black, Blue, Red, White, etc.



CSAT-M07VDG0-B2

- ▶ Vertical DIP, Type B Footprint
- ▶ B2: Pin=2.15~2.3mm; B3: Pin=3.3mm
- ▶ Color Options: Black, Blue, Red, White, etc.



CSAT-M07VDG0-C2

- ▶ Vertical DIP, Type C Footprint
- ▶ C2: Pin=2.10mm (SATA3)
- ▶ Color Options: Black, Blue, Red, White, etc.



CSAT-M07VD30-AB

- ▶ Male, Vertical, DIP, 2 Arms, Black Color



CSAT-M07VS30-XX

- ▶ Male, Vertical, SMT Version,
- ▶ Shrouded Housing



CSAT-M07VD30-AK

- ▶ Male, Vertical, DIP, With Shielding



CSAT-M07RS30-S1

- ▶ Male, R/A, Standard, SMT,
- ▶ 2 Arms (DIP Type Available)



CSAT-M07RS30-S4

- ▶ Male, R/A, Standard, SMT,
- ▶ Shrouded Housing (DIP Type Available)



CSAT-M07RS30-R4

- ▶ Male, R/A, Reversed, SMT, 2 Arms
- ▶ (DIP Type Available)




CSAT-M07RS30-SA

- ▶ Male, R/A, Standard, SMT, Shielding



CSAT-M142DG0-S1

- ▶ Male, Stacked, DIP, 2Ports,
- ▶ Color Options: Black, Blue, Red, etc.



CSAT-M14VD30-AD

- ▶ Male, Vertical, DIP, 2Ports,
- ▶ (AD=2.05mm, AE=3.3mm)



CSAT-F07SS30-EC

- ▶ Female, Straddle, SMT



CSAT-M15RD30-PB

- ▶ Male, R/A, Standard, DIP (SATA 15P Power)



CSAT-M18VD30-E2

- ▶ Male, Vertical, DIP (SATA Express, 7+7+4P)



Connectors Specialist, We Connect Your Quality Systems.
Cables Assembly, We Link Your Innovation Projects.

www.conn-link.com.tw

Serial ATA 22P Male Connectors



CSAT-M22RS30-HA
▶ R/A, SMT, Standard Type, DIP Harpoon



CSAT-M22RD30-HB
▶ R/A, Single Row DIP, Standard Type



CSAT-M22VD30-HE
▶ Vertical, Single Row DIP,
▶ (HE=2.1mm, HF=3.0mm)



CSAT-M22VD30-HG
▶ Vertical, Double Row DIP,
▶ (HG=2.1mm, HH=3.0mm)



CSAT-M22VS30-HD
▶ Vertical, SMT Type



CSAT-M22SS30-HC
▶ Straddle, SMT, 1.0mm PCB Thickness



CSAT-M22RD30-S2
▶ R/A, Double Row DIP,
▶ Standard Type, With Shrouded



CSAT-M22RS30-S3
▶ R/A, SMT, Standard Type



CSAT-M22RS30-R5
▶ R/A, SMT, Reverse Type, H=4.5mm
▶ (R8=with CAP H=4.0mm)



CSAT-M221S30-S6
▶ Subside, SMT, Standard Type,
▶ H=4.0mm Height



CSAT-M221S30-R7
▶ Subside, SMT, Reverse Type,
▶ Body=8.53mm



CSAT-M221S30-R9
▶ Subside, SMT, Reverse Type,
▶ Body=8.10mm



Serial ATA 22P Female Connectors



CSAT-F22RS30-S6

- ▶ R/A, SMT, Standard Type, H=6.7mm
- ▶ (S2=4.3mm, S3=5.0mm, S8=7.5mm)



CSAT-F221D30-P6

- ▶ Subside, DIP, Standard Type, H=3.0mm



CSAT-F221S30-O6

- ▶ Subside, SMT, Standard Type, With Screw Holes



CSAT-F22SS30-03 (04)

- ▶ Straddle Type, SMT, for 1.0mm PCB Thickness
- ▶ (04=for 1.6mm PCB Thickness)



CSAT-F22SS30-24 (25)

- ▶ Straddle Type, Double Row SMT, for PCB 1.0mm Thickness
- ▶ (25=Body 5.0mm)



CSAT-F22VS30-13

- ▶ Vertical, SMT, With SMT Harpoon, H=10.7mm



CSAT-F22VS30-14

- ▶ Vertical, SMT, With Plastic Post, H=9.85mm, Reverse



CSAT-F22VD30-08

- ▶ Vertical, Double Row, DIP, H=10.7mm



CSAT-F22VD30-11

- ▶ Vertical, Double Row, DIP, H=9.85mm, Harpoon Posts



CSAT-F22VD30-0D

- ▶ Vertical, Single Row, DIP, H=9.85mm, Harpoon Posts



CSAT-F22VD30-07

- ▶ Vertical, Single Row, DIP, H=15.85mm High Profile, Plastic Post, Post Board 2.9mm



Connectors Specialist, We Connect Your Quality Systems.
Cables Assembly, We Link Your Innovation Projects.

www.conn-link.com.tw

Micro SATA 16P Connectors



CSAT-M161S30-V3(V6)
▶ Male, Subside, SMT (V6=With CAP)



CSAT-M16SS30-V7
▶ Male, Straddle, SMT



CSAT-F16RS30-U3
▶ Female, R/A, SMT, Standard Type,
H=4.55mm



CSAT-F16V330-U6
▶ Female, Vertical, Solder Type



CSAT-716CD30-J1
▶ Micro SATA 16P Female to 7P Male Coupler



CASE-18SSD-N1U
▶ 1.8" SATA SSD Case

Slim Line SATA 13P Connectors



CSAT-M13RS30-Q3
▶ Male, R/A, SMT, Standard Type,
▶ With Ring Pad (Q4: With Harpoon Pad)



CSAT-F13VD30-N1
▶ Female, Vertical, DIP, H=9.8mm,
▶ With SMT Harpoon, With Posts



CSAT-F13VS30-N6
▶ Female, Vertical, SMT, H=9.8mm,
▶ With SMT Harpoon, With Posts



CSAT-F13RD30-G2
▶ Female, R/A, DIP, Standard Type,
▶ H=3.75mm, With Screw Holes (S2=With Screw)



CSAT-F13RS30-G3
▶ Female, R/A, SMT, Reverse Type,
▶ H=5.80mm, With Screw Holes (S3=With Screw)



CSAT-F13RS30-G6
▶ Female, R/A, SMT, Standard Type,
▶ H=12.10mm, With Screw Holes (S6=With Screw)



CSAT-F13RS30-GA
▶ Female, R/A, SMT, Standard Type,
H=4.50mm



CSAT-F13RS30-GE
▶ Female, R/A, SMT, Standard Type,
▶ H=6.10mm, Without Post, With CAP



CSAT-C13C0G0-M9
▶ Slim Line SATA 13P Female to 13P Male Coupler



eSATA (external SATA) Connectors



CEAT-M07UD3R-R4
► Upright, DIP, Red Color (Black Color Option)



CEAT-M07RD30-B1
► R/A, DIP, Standard Type



CEAT-M07RS30-B3
► R/A, SMT, Standard Type



CEAT-M07RS30-B6
► R/A, SMT, Reverse Type



CEAT-M07RD30-B4
► R/A, DIP, Reverse Type



CEAT-M07RS30-C3
► R/A, SMT, Standard Type, Without Spring



CEAT-M07VD30-M1
► Male, Vertical, DIP



CEAT-M07VS30-M2
► Male, Vertical, SMT



CEAT-M07RS3R-S1
► Slim eSATA, R/A, SMT, Standard Type



CEAT-M142D3Y-D4
► Dual eSATA, Stacked, DIP
► (Black, Red or Yellow)



CEAT-M142D3R-E4
► Dual eSATA, Stacked, DIP
► (Black, Red or Yellow)



CUIE-M212DGY-72
► 2*USB+IEEE 1394+eSATA,
► Stacked, DIP (Red or Yellow)



CEUS-M112D3R-11
► USB+eSATA, Stacked, DIP
► (Red or Yellow)



CEUS-M152D3R-21
► 2*USB+eSATA, Stacked, DIP
► (Red or Yellow)



CEUS-M222DGY-32
► 2*USB+2*eSATA, Stacked, DIP
► (Red or Yellow)



Connectors Specialist, We Connect Your Quality Systems.
Cables Assembly, We Link Your Innovation Projects.

www.conn-link.com.tw

SAS (Serial Attached SCSI) Connectors



CSAS-F29VP40-P1

► Female, Vertical, Press Fit



CSAS-F29VD40-D1

► Female, Vertical, Single Row, DIP, H=9.85mm



CSAS-F29VS40-D3

► Female, Vertical, SMT, H=9.85mm



CSAS-F29VS40-F6

► Female, Vertical, SMT, with Plastic Posts



CSAS-F29VD40-F1

► Female, Vertical, Double Row,
► DIP=2.6mm (F2: DIP=3.5mm)



CSAS-F29V240-D6

► Female, Vertical, DIP+SMT,
► H=15.95mm High Profile



CSAS-F29V240-DA

► Female, Vertical, DIP+SMT, H=9.85mm



CSAS-F29RS40-F3

► Female, R/A, SMT, Reverse, H=6.7mm



CSAS-F29SS40-F4

► Female, Straddle, SMT, for 1.6mm PCB
Thickness



CSAS-M29SS40-M4(M6)

► Male, Straddle, SMT. For 1.0mm PCB
Thickness (M6=1.6mm)



CSAS-M29VD40-M1

► Male, Vertical, Single Row DIP, 2.1mm



CSAS-M29VS40-M7

► Male, Vertical, SMT, With Screw Holes



CSAS-M29RS40-M3

► Male, R/A, SMT, Standard Type, H=4.0mm



CSAS-M29RS40-M5

► Male, R/A, SMT, Reverse Type, H=6.95mm



CSAS-M29RS40-M8

► Male, R/A, SMT, Reverse Type, H=4.0mm



HDMI (High Definition Multimedia Interface)



CHDM-P19RS30-03
▶ R/A, SMT, Without Flange, Without Post



CHDM-P19RS30-05
▶ R/A, SMT, Without Flange, With Post



CHDM-P19UD30-0R
▶ Upright Type, 2Rows DIP, Without Flange



CHDM-P19RS30-F3 (F5)
▶ R/A, SMT, With Flange H*W=8.2mm*7.5mm,
▶ Without Post (F5=With Posts)



CHDM-P19RS30-H3 (H5)
▶ R/A, SMT, With Flange
H*W=10.3mm*7.5mm,
▶ Without Post (H5=With Posts)



CHDM-P19VS30-FV
▶ Vertical, SMT, With Flange



CHDM-P19RD30-01
▶ R/A, 2Rows DIP, Without Flange
▶ (Flange Options: F1, H1, L1)



CHDM-P19RD30-06
▶ R/A, 3Rows DIP, Without Flange
▶ (Flange Options: F6, C6)



CHDM-P19RD30-0A
▶ R/A, 2Rows DIP, Reverse Type, Without Flange



CHDM-P191D30-02
▶ Subside, 2Rows DIP, H=3.37mm



CHDM-P191D30-09
▶ Subside, 2Rows DIP, Reverse Type,
H=4.55mm



CHDM-P191D30-0E
▶ Subside, 2Rows DIP, Reverse Type,
H=1.90mm



CHDM-P232DG0-U7
▶ USB+HDMI, Stacked, DIP



CHDM-M19SS30-11
▶ Male Type, Straddle, SMT



CHDM-M19SS30-12
▶ Male Type, Straddle, SMT, with Harpoon



CHDC-P19RS30-00
▶ Mini HDMI (Type C), R/A, SMT



CHDD-P19R230-10
▶ Micro HDMI (Type D), R/A, SMT+DIP



Connectors Specialist, We Connect Your Quality Systems.
Cables Assembly, We Link Your Innovation Projects.

www.conn-link.com.tw

Display Connectors



CDVI-F24RDG1-P1

► DVI-D, 24P, Female, R/A, DIP



CDVI-F29RDG1-P1

► DVI-I, 29P, Female, R/A, DIP



CDVI-F24VDG1-P1

► DVI-D, 24P, Female, Vertical, DIP



CDVI-F29VDG1-P1

► DVI-I, 29P, Female, Vertical, DIP



CDPC-R20RS40-E3

► DisplayPort, 20P, Receptacle, R/A, SMT



CDPC-R20RS40-F3

► DisplayPort, 20P, Receptacle, R/A,
► SMT, With Flange 14.9*9.22mm



CDPC-R20RS40-G3

► DisplayPort, 20P, Receptacle, R/A,
► SMT, With Flange 7.0*8.1mm



CDPC-R20RD40-E5

► DisplayPort, 20P, Receptacle,
► R/A, 2Rows DIP



CDPC-R20RD40-E6

► DisplayPort, 20P, Receptacle,
► R/A, 3Rows DIP



CDPC-P20V340-C1

► DisplayPort, 20P, Plug, for Cable Assembly



CMDP-R20R240-R1(R2)

► Mini DisplayPort (MDP), 20P, Receptacle,
R/A, H=5.5mm, SMT+DIP(R1=2.3mm,
R2=3.1mm)



CMDP-R20R240-R8(R9)

► Mini DisplayPort (MDP), 20P, Receptacle,
R/A, H=3.2mm, SMT+DIP(R8=2.3mm,
R9=3.1mm)



CMDP-R20R240-RA(RB)

► Mini DisplayPort (MDP), 20P, Receptacle,
R/A, H=3.8mm, SMT+DIP(RA=2.3mm,
RB=3.1mm)



CTDB-R20R240-T1

► Thunderbolt, 20P, Receptacle, R/A,
► H=3.2mm, SMT+DIP(2.3mm)



CMDP-R20V340-R7

► Mini DisplayPort (MDP) 20P,
► Receptacle, Solder Type



CMDP-P20V341-P7

► Mini DisplayPort (MDP) 20P,
► Plug, for Cable Assembly



USB Connectors



CU2A-R04RDG1-11

- ▶ A Type, Receptacle, R/A, DIP
- ▶ (1=White Color, 0=Black Color)



CU2A-R04VDG1-12

- ▶ A Type, Receptacle, Vertical, DIP
- ▶ (1=White Color, 0=Black Color)



CU2A-R04UDG1-13

- ▶ A Type, Receptacle, Upright, DIP
- ▶ (1=White Color, 0=Black Color)



CU2A-R04RSG1-14

- ▶ A Type, Receptacle, R/A,
- ▶ SMT, White Color



CU2A-R082DG0-01

- ▶ A Type, Receptacle, Dual Ports,
- ▶ Stacked, DIP



CU2A-R082DG0-S1

- ▶ A Type, Receptacle, Dual Ports,
- ▶ Stacked, DIP, Spring Shielding



CU2A-P041SG0-16

- ▶ A Type, Plug, Subside, SMT



CU2B-R04RDG1-11

- ▶ B Type, Receptacle, R/A, DIP
- ▶ (1=White Color, 0=Black Color)



CU2B-R04VDG1-12

- ▶ B Type, Receptacle, Vertical, DIP
- ▶ (1=White Color, 0=Black Color)



CU2N-R05RSG0-11

- ▶ Mini B Type, R/A, SMT



CU2N-R05RDG0-11

- ▶ Mini B Type, R/A, DIP



CU2N-R05VDG0-12

- ▶ Mini B Type, Vertical, DIP



CU2N-R05RSG0-14

- ▶ Mini AB Type, R/A, SMT



CU2M-R05RSG0-11

- ▶ Micro B Type, R/A, SMT,
- ▶ SMD Shielding



CU2M-R05RSG0-12

- ▶ Micro B Type, R/A, SMT,
- ▶ DIP Shielding



Connectors Specialist, We Connect Your Quality Systems.
Cables Assembly, We Link Your Innovation Projects.

www.conn-link.com.tw

USB3.0 Connectors



CU3M-R10RS40-12(11)

▶ Micro AB Type, R/A, SMT
▶ (11=SMT Shielding, 12=DIP Shielding)



CU3M-R10RS40-22(21)

▶ Micro B Type, R/A, SMT
▶ (21=SMT Shielding, 22=DIP Shielding)



CU3M-R10VS40-23

▶ Micro B Type, Vertical, SMT, H=6.0mm



CU3A-P09V34B-30

▶ A Type, Plug for Cable Assembly



CU3A-R09RD4B-01

▶ A Type, Receptacle, R/A,
▶ DIP, Blue Color



CU3A-R09VD4B-V1

▶ A Type, Receptacle, Vertical,
▶ DIP, Blue Color



CU3A-P091S4B-31

▶ A Type, Plug, Subside, SMT, H=3.1mm



CU3A-P091S4B-33

▶ A Type, Plug, Subside, SMT, H=1.9mm



CU3A-R182D4B-21(22)

▶ A Type, Receptacle, Dual Port,
▶ Stacked, DIP (21=2.15mm, 22=3.10mm)




CU3A-R182D4B-23(24)

▶ A Type, Receptacle, Dual Port, Stacked,
▶ DIP, Short Body (23=2.15mm, 24=3.10mm)



CU3B-R09RD4B-02

▶ B Type, Receptacle, R/A, DIP



CU3B-R09VD4B-00

▶ B Type, Receptacle, Vertical, DIP



CU3B-P09V34B-30

▶ B Type, Plug for Cable Assembly



CU3I-M19VDGB-I1

▶ Internal Type, Vertical, DIP
▶ (0=Black Color, B=Blue Color)



CU3I-M19RDGB-I3

▶ Internal Type, R/A, DIP
▶ (0=Black Color, B=Blue Color)



DC Power Jack (DIP Type)



CDCJ-XX3RDT0-50

- ▶ R/A, DIP, XX=Center Pin
- ▶ (2.0mm, 2.35mm, or 2.5mm)



CDCJ-XX3RDT0-5K

- ▶ R/A, DIP, With Kink Pin,
- ▶ XX=Center Pin (2.0mm, 2.35mm, or 2.5mm)



CDCJ-XX3VDT0-5A

- ▶ Vertical, DIP, XX=Center Pin
- ▶ (2.0mm, 2.35mm, or 2.5mm)



CDCJ-XX3RDT0-44

- ▶ R/A, DIP, XX=Center Pin
- ▶ (2.0mm or 2.5mm)



CDCJ-XX3VDT0-15

- ▶ Vertical, DIP, With PCB,
- ▶ XX=Center Pin (2.0mm or 2.5mm)



CDCJ-XX3VDT0-16

- ▶ Vertical, DIP, With PCB,
- ▶ XX=Center Pin (2.0mm or 2.5mm)



CDCJ-XX3VDT0-17

- ▶ Vertical, DIP, With Screw Holes,
- ▶ XX=Center Pin (2.0mm or 2.5mm)



CDCJ-XX3VDT0-18

- ▶ Vertical, DIP, With Screw Holes,
- ▶ XX=Center Pin (2.0mm or 2.5mm)



CDCJ-XX3UDT0-47

- ▶ Upright, DIP, With Shielding,
- ▶ XX=Center Pin (2.0mm or 2.5mm)



CDCJ-XX3RDB0-01

- ▶ R/A, DIP, XX=Center Pin
- ▶ (1.0mm, 1.3mm, or 1.65mm)



CDCJ-XX3RDB0-02

- ▶ R/A, DIP, XX=Center Pin
- ▶ (1.0mm, 1.3mm, or 1.65mm)



CDCJ-XX3RDB0-06

- ▶ R/A, DIP, XX=Center Pin
- ▶ (1.0mm, 1.3mm, or 1.65mm)



CDCJ-XX3VDT0-MB

- ▶ Vertical, DIP, With Screw,
- ▶ XX=Center Pin (2.0mm, or 2.5mm)



CDCJ-XX3RDT0-M4

- ▶ R/A, DIP, With Screw,
- ▶ XX=Center Pin (2.0mm, or 2.5mm)



CDCJ-XX3RDT0-38

- ▶ R/A, DIP, XX=Center Pin
- ▶ (2.0mm, or 2.5mm)



CDCJ-XX3RDT0-39

- ▶ R/A, DIP, XX=Center Pin
- ▶ (2.0mm, or 2.5mm)



Connectors Specialist, We Connect Your Quality Systems.
Cables Assembly, We Link Your Innovation Projects.

www.conn-link.com.tw

DC Power Jack (SMT Type)



CDCJ-XX3RST0-5S

► R/A, SMT, XX=Center Pin
► (2.0mm, 2.35mm, or 2.5mm)



CDCJ-XX3RSB0-03

► R/A, SMT, XX=Center Pin
► (1.0mm, 1.3mm, or 1.65mm)



CDCJ-XX3RSB0-05

► R/A, SMT, XX=Center Pin
► (1.0mm, 1.3mm, or 1.65mm)



CDCJ-063RSB0-61

► R/A, SMT, Center Pin=0.65mm



CDCJ-063RSB0-65

► R/A, SMT, Center Pin=0.65mm



CDCJ-133RSB0-92

► R/A, SMT, Center Pin=1.35mm

Power Connectors



CPDJ-F03RDB0-00

► Power Din Jack, 3P, R/A,
► DIP, Without Shielding



CPDJ-F04RDB0-00

► Power Din Jack, 4P, R/A,
► DIP, Without Shielding



CPDJ-F04RDB0-05

► Power Din Jack, 4P(or 3P),
► R/A, DIP, With Shielding



CATX-MXXVDT1-50

► ATX Power, XXPins, Vertical,
► DIP, Without Posts



CATX-MXXVDT1-51

► ATX Power, XXPins, Vertical,
► DIP, With Posts



CATX-MXXRDT1-52

► ATX Power, XXPins, R/A,
► DIP, Without Posts



CP4P-M04VDT1-D5

► Power 4P, Vertical, DIP
► (D5=Without Posts, D7=With Posts)



CP4P-M04RDT1-D2

► Power 4P, R/A, DIP, With Posts



CBAH-002RDT0-A3

► Battery Holder, R/A, DIP, CR2032



CBAH-002VDT0-B3

► Battery Holder, Vertical, DIP, CR2032



3.5mm Earphone Jack



CEPJ-3XXUDTG-55
► Upright, DIP, Green (Black, Blue, or Pink)



CEPJ-3XXRDBP-S7
► R/A, DIP, With Spring,
► Pink (Black, Blue, or Green)



CEPJ-3XXRDBG-58
► R/A, DIP, Azalia, Green (Pink or Blue)



CEPJ-323VDB0-M1
► Vertical, DIP, With Screw



CEPJ-323RDB0-M2
► R/A, DIP, With Screw



CEPJ-3XXRDTT-M4
► R/A, DIP, With Screw



CEPJ-323RDB0-5D
► R/A, DIP, Metal Ring



CEPJ-3XXRDBG-5C
► R/A, DIP, Green (Black, Blue, or Pink)



CEPJ-3H7RDB0-5B
► R/A, DIP, 7P, 4Poles



CEPJ-3B51SG0-3A
► Subside, SMT



CEPJ-3XXRSB0-31
► R/A, SMT, Black



CEPJ-3G6RSG0-32
► R/A, SMT, 6P, 4Poles



CEPJ-3E6RSB0-36
► R/A, SMT, 6P, 3Poles



CEPJ-3XXRSB0-37
► R/A, SMT, 4Poles



CEPJ-3C5RSG0-38
► R/A, SMT, 5P, 3Poles



Connectors Specialist, We Connect Your Quality Systems.
Cables Assembly, We Link Your Innovation Projects.

www.conn-link.com.tw

2.5mm Earphone Jack



CEPJ-2XXRSG0-2A
▶ 2.5mm Earphone Jack, R/A, SMT



CEPJ-2XXRSB0-21
▶ 2.5mm Earphone Jack, R/A, SMT



CEPJ-2XXRDB0-22
▶ 2.5mm Earphone Jack, R/A, DIP



CEPJ-2XXRSG0-23
▶ 2.5mm Earphone Jack, R/A, SMT



CEPJ-2XXRSG0-24
▶ 2.5mm Earphone Jack, R/A, SMT



CEPJ-2XXRSG0-25
▶ 2.5mm Earphone Jack, R/A, SMT



CEPJ-2XXRSB0-27
▶ 2.5mm Earphone Jack, R/A, SMT



CEPJ-244RDT0-52
▶ 2.5mm Earphone Jack, R/A, SMT

D-SUB Connector



CDSB-FXXRDG0-X1
▶ D-SUB, Female, R/A, DIP
▶ (XX=9P, 15P, 25P, 37P)



CDSB-MXXRDG0-X1
▶ D-SUB, Male, R/A, DIP
▶ (XX=9P, 15P, 25P, 37P)



CDSB-FXXVDG0-X6
▶ D-SUB, Female, Vertical, DIP
▶ (XX=9P, 15P, 25P, 37P)



CDSB-MXXVDG0-X6
▶ D-SUB, Male, Vertical, DIP
▶ (XX=9P, 15P, 25P, 37P)



CDSB-H242DG9-XG
▶ D-SUB, 9M+15F, Stacked, DIP



CDSB-M182DGG-XG
▶ D-SUB, 9M+9M, Stacked, DIP



CDSB-F15RDGB-XX
▶ D-SUB, VGA, 15P, Female, R/A, DIP



CDSB-F15RDGB-NR
▶ D-SUB, VGA, 15P, Female, Slim Type



RJ Modular Jack



CRJM-188RDG0-S1

- ▶ Side Entry, With Shielding,
- ▶ With Spring, LED Options



CRJM-188RDG0-S0

- ▶ Side Entry, With Shielding,
- ▶ With Spring, Without LED



CRJM-188RDG0-R4

- ▶ Side Entry, With Shielding,
- ▶ Without Spring, LED Options



CRJM-488RDG0-S1

- ▶ Side Entry, 1*4Ports, With Shielding,
- ▶ With Spring, LED Options



CRJM-488RDGY-Q0

- ▶ Side Entry, 1*4Ports,
- ▶ Without Shielding, Without LED



CRJM-188RDG0-C0

- ▶ Side Entry, Without Shielding, Without LED



CRJM-188RSG0-C0

- ▶ Side Entry, SMT, Without Shielding, Without LED



CRJM-188RDG0-A0

- ▶ Side Entry, With Shielding, Without LED



CRJM-188RDG0-B4

- ▶ Side Entry, With Shielding,
- ▶ Shielding DIP Between Pin and Posts, LED Options



CRJM-188RDG0-E0

- ▶ Side Entry, Long Body,
- ▶ Shielding DIP Between Pin and Posts



CRJM-2842DG0-00

- ▶ 2Ports, 8P4C, Stacked, Shielding



CRJM-288C0GX-Z2

- ▶ RJ Modular Coupler, Cat 5e



CRJM-288C0GX-Z4(Z5)

- ▶ RJ Modular Coupler, Cat 3,
- ▶ With Shielding (Z5: Without Shielding)



CRJM-266C0G0-Z8

- ▶ RJ Modular Coupler,
- ▶ 6P6C Without Shielding



CRJM-288C051-ZA

- ▶ RJ Modular Coupler,
- ▶ Cat 6, With Shielding



Connectors Specialist, We Connect Your Quality Systems.
Cables Assembly, We Link Your Innovation Projects.

www.conn-link.com.tw

RJ Modular Jack



CRJM-188VDG0-P0

► Top Entry, 8P8C, Press Fit



CRJM-188VDG0-L0

► Top Entry, Low Profile, DIP



CRJM-188VDG0-H0

► Top Entry, DIP, H Housing



CRJM-188VDG0-I0

► Top Entry, DIP, I Type Shielding



CRJM-188VDG0-J0

► Top Entry, DIP, J Type Shielding



CRJM-188VDG0-K0

► Top Entry, DIP, K Housing



CRJM-18AVD10-14

► Top Entry, 8P10C, DIP

Optical Jack



CSPJ-T03RDT0-02

► Toslink, R/A, DIP, With Flange Hole,
► Transmitter TX (R03=Receiver RX)



CSPJ-T03RDT0-03

► Toslink, R/A, DIP,
► Transmitter TX (R03=Receiver RX)



CSPJ-T03RDT3-04

► Toslink, R/A, DIP, Gray Gap,
► Transmitter TX (R03=Receiver RX)



CSPJ-T03RDTG-18

► Toslink, R/A, DIP, Green Gap,
► Transmitter TX



CSPJ-R03RDTP-18

► Toslink, R/A, DIP, Pink Gap,
► Receiver RX



CSPJ-R232DT0-B6

► RCA+Toslink, Stacked,
► Pink Gap, Receiver RX



Pin Header



CP12-2XXVSG0-19

► Pitch 1.27mm, 2*XXP, Vertical, SMT,
► Dual Housing, Plastic Posts



CP12-2XXVSG0-18

► Pitch 1.27mm, 2*XXP, Vertical,
► SMT, Plastic Posts



CP12-2XXRDG0-10

► Pitch 1.27mm, 2*XXP, R/A, DIP



CP12-1XXVSG0-10

► Pitch 1.27mm, 1*XXP, Vertical, SMT



CP12-1XXVSG0-10

► Pitch 1.27mm, 1*XXP, Vertical, DIP



CP20-1XXVDG0-10

► Pitch 2.0mm, 1*XXP, Vertical, DIP



CP20-2XXVDG0-10

► Pitch 2.0mm, 2*XXP, Vertical, DIP



CP20-1XXRDG0-10

► Pitch 2.0mm, 1*XXP, R/A, DIP



CP20-2XXRDG0-10

► Pitch 2.0mm, 2*XXP, R/A, DIP




CP20-2XXVSG0-10

► Pitch 2.0mm, 2*XXP, Vertical, SMT



CP25-2XXVSG0-10

► Pitch 2.54mm, 2*XXP, Vertical, SMT



CP25-1XXVDG0-00

► Pitch 2.54mm, 1*XXP, Vertical, DIP




CP25-2XXVDG0-00

► Pitch 2.54mm, 2*XXP, Vertical, DIP



CP25-1XXRDG0-00

► Pitch 2.54mm, 1*XXP, R/A, DIP



CP25-2XXRDG0-00

► Pitch 2.54mm, 2*XXP, R/A, DIP



CP25-2XXVDG0-15

► Pitch 2.54mm, 2*XXP,
► Vertical, DIP, T=15mm



Connectors Specialist, We Connect Your Quality Systems.
Cables Assembly, We Link Your Innovation Projects.

www.conn-link.com.tw

Box Header



CB12-2XXRDG0-10
▶ Pitch 1.27mm, 2*XXP, R/A, DIP



CB12-2XXVDG0-10
▶ Pitch 1.27mm, 2*XXP, Vertical, DIP



CB20-2XXVDG0-1L
▶ Pitch 2.0mm, 2*XXP, Vertical,
▶ DIP, High Profile



CB20-2XXVDG0-1K
▶ Pitch 2.0mm, 2*XXP, Vertical,
▶ DIP, M Type Housing



CB20-2XXVDG0-10
▶ Pitch 2.0mm, 2*XXP, Vertical, DIP



CB20-2XXRDG0-10
▶ Pitch 2.0mm, 2*XXP, R/A, DIP



CB20-2XXVSG0-10
▶ Pitch 2.0mm, 2*XXP, Vertical, SMT



CB25-2XXVDG0-00
▶ Pitch 2.54mm, 2*XXP, Vertical, DIP



CB25-2XXRDG0-00
▶ Pitch 2.54mm, 2*XXP, R/A, DIP



CB25-2XXVSG0-00
▶ Pitch 2.54mm, 2*XXP, Vertical, SMT



Female Header



CF12-2XXVSG0-B7

- ▶ Pitch 1.27mm, 2*XXP, Vertical,
- ▶ SMT, With Metal Cap



CF12-2XXRDG0-16

- ▶ Pitch 1.27mm, 2*XXP,
- ▶ R/A, DIP, H=4.0mm



CF12-2XXVDG0-11

- ▶ Pitch 1.27mm, 2*XXP,
- ▶ Vertical, DIP, H=4.0mm



CF20-2XXRDG0-03

- ▶ Pitch 2.0mm, 2*XXP, R/A,
- ▶ DIP, Body H=4.3mm



CF20-1XXVDG0-03

- ▶ Pitch 2.0mm, 1*XXP,
- ▶ Vertical, DIP, H=4.3mm




CF20-2XXVDG0-03

- ▶ Pitch 2.0mm, 2*XXP,
- ▶ Vertical, DIP, H=4.3mm




CF25-1XXVDG0-00

- ▶ Pitch 2.54mm, 1*XXP,
- ▶ Vertical, DIP, H=8.4mm




CF25-2XXVDG0-00

- ▶ Pitch 2.54mm, 2*XXP,
- ▶ Vertical, DIP, H=8.4mm



CF25-1XXRDG0-00

- ▶ Pitch 2.54mm, 1*XXP, R/A,
- ▶ DIP, Body H=8.4mm



CF25-2XXRDG0-00.psd

- ▶



Connectors Specialist, We Connect Your Quality Systems.
Cables Assembly, We Link Your Innovation Projects.

www.conn-link.com.tw

Wafer & FPC Connectors



CW10-MXXRST1-R4
► Pitch 1.0mm, Wafer, XXP, R/A, SMT



CW12-MXXVDT1-47
► Pitch 1.25mm, Wafer, XXP, Vertical, DIP



CW12-MXXVST1-V7
► Pitch 1.25mm, Wafer, XXP, Vertical, SMT



CW12-MXXRDT1-R7
► Pitch 1.25mm, Wafer, XXP, R/A, DIP



CW12-MXXRST1-H7
► Pitch 1.25mm, Wafer, XXP, R/A, SMT



CW15-MXXVKT4-74
► Pitch 1.50mm, Wafer, XXP, Vertical, Kink DIP



CW20-MXXRST1-R1
► Pitch 2.0mm, Wafer, XXP, R/A, SMT



CW24-MXXVDT1-01
► Pitch 2.5mm, Wafer, XXP, Vertical, DIP



CW39-MXXVDT1-20
► Pitch 3.96mm, Wafer, XXP, Vertical, DIP



CFPC-1XXBDT1-B3
► FPC ZIF Connector, 0.5mm Pitch, Bottom Contact



CFPC-1XXTDT1-B3
► FPC ZIF Connector, 0.5mm Pitch, Top Contact



CFPC-1XXPLG1-D3
► FPC ZIF Connector, 0.5mm Pitch, Gold Flash



CFPC-1XXVDT1-V3
► FPC ZIF Connector, 0.5mm Pitch, Top Contact



Cable Assembly



LSAT-SATA Cable



LEST-eSATA Cable



LSAS-SAS Cable



LUSB-USB2.0 Cable



LUSB-USB3.0 Cable



LUSB-Flourescent USB Cable



LHDM-Flourescent HDMI Cable



LHDM-HDMI Cable



LDPC-DisplayPort Cable



LMDP-Mini DisplayPort Cable



LDVI-DVI Cable



LCAV-Control Active Vedio Cable



LBNC-BNC Cable



LRCA-RCA Cable



LACP-AC Power Code



LFFC-FFC Cable



LHCA-Wire Harlness Cable



Connectors Specialist, We Connect Your Quality Systems.
Cables Assembly, We Link Your Innovation Projects.

www.conn-link.com.tw

► Equipments

Conn-Link Technology Inc. supports customers the best services association, to provide customers' innovation, high quality and competitive projects. Our factories not only improve our Research & Development technologies and Quality Control systems, but also setup a coup of high precision equipments based on our production inquire. We also upgrade and increase our equipments if production process is necessary.



Equipments of Cable Assembly Factory :

- Circle cable Extruder: 20Sets
- Flat cable Extruder: 3Sets
- Knitting machine: 135Sets
- Twist Copper machine : 30Sets
- Enlacing machine : 20Sets
- Winding machine : 20Sets
- Molding machine : 29 Sets
- Production lines : 15 ropes



Equipments of Connector Factory :

- High-Speed Continuous Automatic Punch
- Plastic Injection Machine
- Insert Molding Machine
- Precision Optical Milling Machine
- Precision Surface-Grinding Machine
- Numeral Control Wire Cut Machine
- Precision Electric Discharge to process Machine
- Assembly Machine Series
- Terminal Cutting Machine Series
- Mold Temperature Controller
- Cabinet Dryer
- Plastic Deflasher



► Quality Assurance

> Quality Policy :

Conn-Link Technology Products are based on customer require, and concerned Product Quality and Environment Protection. Through execute the continuous improvement on quality to fulfill customer' s requirement.

> Quality Promise :

Conn-Link' s quality is started from research & development. Because of the years design experience, and follow up continuous improvements, we accumulated the quality design knowledge. Conn-Link pre-controls the best quality in the R&D stage. So, we can provide the quality promise for our customers.

> Quality Control Process :

Conn-Link' s quality is started from R&D, and held the spirit of the “Quality First and Continuous Improvements.” From Tooling Design → IQC → IPQC → FQC → OQC, we implement the quality control process strictly to achieve the high level quality assurance.

> Green Environment Policy :

Conn-Link' s products are started from the Green Environment Concern to design for Innovation and Quality. We hope to create an ECO production resource, thus, all of our products are RoHS compliance, and most are REACH and Halogen Free.

> Quality Equipments :



- High Magnification Microscope
- High Magnification Projector
- Micro Ohm Meter Machine
- Voltage Resistance Testing Machine
- Temperature Control Solder Stove
- Insertion and Extraction Force Testing Machine
- Hardness Testing Machine
- X-Ray
- Durability Testing Maching
- Environment Ageing Testing Equipments
- IR Reflow
- Salt Spray Testing Machine
- Automated Testing Machine
- XRF Machine (RoHS)
- CCD
- Spectrophotometer



凱聯科技股份有限公司 Conn-Link Technology Inc.

24747新北市蘆洲區集賢路240號13樓

13F, No. 240, Jixian Rd., Lu-Zhou District, New Taipei City 24747, Taiwan

Tel : +886 2 8282-5192 Rep. Fax : +886 2 8282-5193

e-Mail : sales@conn-link.com.tw

Web Side : <http://www.conn-link.com.tw>

統一編號 : 53203243