

Signal Segment			
Pin NO.	Type	Name	Type
S1	Signal Ground	S8	Signal Ground
S2	TP+	S9	TS+
S3	TP-	S10	TS-
S4	Signal Ground	S11	Signal Ground
S5	RP-	S12	RS-
S6	RP+	S13	RS+
S7	Signal Ground	S14	Signal Ground

Operating Temperature: 0°C to +55°C

- Product Number:
F1: Dual Row, D=2.6mm
- 0: Black Color
- 4: 30u" Plating
- D: DIP Type

A	09/09/10	RELEASED FOR PRODUCTION			
REV	DATE	DESCRIPTION			
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MM TOLERANCES ARE:		CAD GENERATED DRAWING, DO NOT MANUALLY UPDATE		 凱聯科技股份有限公司 Conn-Link Technology Inc.	DESCRIPTION SAS Connector, 7+7+15P Female, Vertical, Dual Row DIP, D=2.6mm, H:9.85mm
DECIMALS ANGLES		APPROVALS DATE			
.X ± .38 ± 3°		DRAWN Chris	09/09/10		
.XX ± .25		CHECKED Cindy	09/09/10		
.XXX ± .20		APPV Jason	09/09/10		
DO NOT SCALE DRAWING		SHEET 1 OF 1	SCALE NONE	DWG. NO.	CSAS-F29-D01
					REV. A