





Unit:mm


Part Number	Dim`A`
CSAT-M07VD30-A2	2.15~2.30
CSAT-M07VD30-A3	3.30



SECT A-A



SECT B-B



P.C.B. Layout
(T=1.60mm)

NOTES:

1. Material:

Housing: Nylon46, UL 94V-0 rated.

Color: Black.

Contact: Brass

Plating: Gold Plating over Nickel on Contact Area.

Tin Plating on Solder tail.

Harpoon: Brass.

Plating: Tin Plating over Nickel.

2. Mechanical:

Insertion Force: 45N Max.

Withdrawal Force: 10N Min.

Durability: 500 Cycles

3. Electrical Specification:

Current Rating: 1.5 Ampere per Contact.

Contact Resistance: 30mΩ Max.

Insulation Resistance: 1000MΩ Min.

Dielectric Withstanding Voltage: 500 VAC.

4. Environmental:

Operating Temperature: -55°C to +85°C

Part Number:

CSAT-M07VD30-A2

Serial ATA Series

M: Male Type

07: 7Pins

V: Vertical Type

D: DIP Type

2: Pin Length 2.15~2.30mm

3: Pin Length 3.30mm

A: Straight DIP Type A

0: Black Color

G: Gold Flash

3: 15u" Plating

A	09/26/07	RELEASED FOR PRODUCTION	
REV	DATE	DESCRIPTION	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MM TOLERANCES ARE:		CAD GENERATED DRAWING, DO NOT MANUALLY UPDATE	
DECIMALS	ANGLES	APPROVALS	DATE
.X ± .38	± 3°	DRAWN Chris	09/26/07
.XX ± .25		CHECKED Cindy	09/26/07
.XXX ± .20		APPV Jason	09/26/07
DO NOT SCALE DRAWING		SHEET 1 OF 1	SCALE NONE
		DWG. NO.	CSAT-M07-031
		REV.	A



凱聯科技股份有限公司
Conn-Link Technology Inc.

Serial ATA, 7P, Male, Shrouded, Vertical Type
DIP Type A 2.15~2.30mm, 15u" Plating, Black Color